

E-band Waveguide Directional Coupler WR-12/20 dB Coupling

Model: TC-060090-20-12

TC-060090-20-12 is a E-band, three-port waveguide directional coupler that delivers a 20 dB nominal coupling level and 35 dB typical directivity across the full waveguide band from 60 to 90 GHz. The interfaces of the coupler are WR-12 waveguides with UG-387/U-M anti-cocking flanges.

Features:

- Operating Frequency: 60 to 90 GHz
- Full Band Operation
- Low Insertion Loss
- Moderate Directivity

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Frequency Range	60		90	GHz
Insertion Loss		1		dB
Coupling		20		dB
Directivity		35		dB
Input VSWR		1.1		:1
Output VSWR		1.1		:1

Environmental And Physical Characteristics:

Description	Parameter	Units
Operating Temperature	-40 To +85	°C
Storage Temperature	-40 to +85	°C
Waveguide Connectors	WR-12/UG-387/U	
Coupled Port	WR-12/UG-387/U	
Size	56*22*22	mm

Outline Drawing:

Unit:mm




ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TC-060090-20-12	E-band Waveguide Directional Coupler,60-90GHz, Insertion Loss:1dB Typ, Coupling:20dB Typ,WR-12	Rev.1.0