

J-band Waveguide Directional Coupler

WR-3.4/20dB Coupling

Model: TDC-220330-20-3.4

TDC-220330-20-3.4 is a J-band, four-port waveguide directional coupler that delivers a 20 dB nominal coupling level and 30 dB typical directivity across the full waveguide band from 220 to 330 GHz. The interfaces of the coupler are WR-3.4 waveguides with UG-387/U-M anti-cocking flanges.

Features:

- Operating Frequency 220 to 330 GHz
- Full Band Operation
- Low Insertion Loss
- Moderate Directivity

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Frequency Range	220		330	GHz
Insertion Loss		3		dB
Coupling		20		dB
Isolation		50		dB
Directivity		30		dB
Input VSWR		1.2		:1
Output VSWR		1.2		:1

Environmental And Physical Characteristics:

Description	Parameter	Units
Operating Temperature	-40 To +85	°C
Storage Temperature	-40 to +85	°C
Waveguide Connectors	WR-3.4/UG-387/U	
Coupled Port	WR-3.4/UG-387/U	
Size	30*36*23	mm

Outline Drawing:

Unit:mm





ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:


Base Number	Description	Revision
TDC-220330-20-3.4	J-band Waveguide Directional Coupler,220-330GHz, Insertion Loss:3dB Typ, Coupling:20dB Typ,WR-3.4	Rev.1.0

Typical Performance Data:


Insertion Loss vs Frequency



Coupling vs Frequency




Isolation vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.