

Model:TLDP-1.4G2.4G-360-6
**6-Bit Digital Phase Shifter
1.4GHz-2.4GHz**
Feature:

- Ultra Wide Band: 1.4-2.4GHz
- High Phase Shift Accuracy
- High Phase Shift Range
- Low Phase Error

Electrical:

Parameter	Min	Typ	Max	Units
Frequency range	1.4-2.4			GHz
Insertion Loss		5		dB
Input VSWR		2		:1
Output VSWR		2		:1
Phase Shift Range		360		°
Phase accuracy		±2		°
Power Handling			27	dBm
Amplitude Balance			±1	dB
Switching speed		100		ns
DC Voltage		-5		V DC
DC Supply Current		30		mA
Number of Bits		6		Bit

Mechanical :


Parameter	Value	Units
Input /Output Connector	SMA Female	
DC and control interface	J30J-9ZKP	
Size	28*20*19.5	mm
Weight	55	g

Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	+5V (±5%)
RF Input Power	27 dBm
ESD sensitivity (HBm)	Class 0, passed 150V

Outline Drawing:

Unit: mm(Inches)



Truth Table						
TTL Control Input						Signal Path State
Bit1	Bit2	Bit3	Bit4	Bit5	Bit6	
0	0	0	0	0	0	Reference
1	0	0	0	0	0	5.625
0	1	0	0	0	0	11.25
0	0	1	0	0	0	22.5
0	0	0	1	0	0	45
0	0	0	0	1	0	90
0	0	0	0	0	1	180
1	1	1	1	1	1	354.375

0(Low)	0V
1 (High)	+3.3V

PIN	1-6	7	8	9
Function	Bit1-Bit6	-5V	NC	GND

Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature	-45		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity		95		%
Altitude	50,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

Ordering Information:

Part Number	Description	Revision
TLDP-1.4G2.4G-360-6	6-Bit Digital Phase Shifter,1.4-2.4GHz,SMA	Rev.1.1