

Model:TMAM-070110-0608-10

V-Band Active Multiplier

X6, 70-110 GHz, +7 dBm Output Power

Feature:

- Output Frequency:70-110 GHz
- Output Power : 7dBm Typ
- Low power consumption

Electrical Specifications:

Parameter	Min	Typ	Max	Units
Output Frequency	70		110	GHz
Output Power		8		dBm
Input Frequency	11.66		18.34	GHz
Input Power	3	5	7	dBm
Harmonic Suppression			-30	dBc
Multiply Factor		6		
DC Voltage		12		V
DC Supply Current		270		mA

Mechanical Specifications:



Parameter	Value	Units
Output Connector	WR-10/UG-387/U	
Input Connector	SMA Female	
Bias	Solder Pin	
Size	46*28*23	mm

Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	TBD
RF Input Power	10 dbm
ESD sensitivity (HBm)	Class 0, passed 150V

Outline Drawing:

Unit: mm



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

Environmental Conditions:


Parameter	Min	Typ	Max	Units
Operating Temperature	-10		+65	°C
Non-operating Temperature	-25		+75	°C
Relative humidity		95		%
Altitude	50,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

Ordering Information:

Part Number	Description	Revision
TMAM-070110-0608-10	Active Multiplier,X6,70-110GHz, Output Power:8dBm,WR-10/UG-387/U,SMA Female	Rev.1.1

Typical Performance Data:

Output Power vs Frequency



Harmonic Suppression vs Frequency

