

Model: TLHM-110170-16-06
Spectrum Analyzer Harmonic Mixer
RF:110-170 GHz,IF:DC-1.8 GHz,16th
Feature:

- Designed for Keysight PXA series and R&S FSW series
- Full Waveguide Band Operation
- Compact Package
- 3 port design
- 16th Harmonic Detection

Electrical Specifications:

参数Parameter	Min	Typ	Max	Units
RF Frequency	110		170	GHz
LO Frequency	6.87		10.625	GHz
IF Frequency	DC		1.8	GHz
LO-Input power		15		dBm
nput Power			0	dBm
RF Input VSWR		3		:1
SSB Conversion Loss	-50	-35	-30	dB

Mechanical Specifications:

Parameter	Value	Units
RF Connector	WR-6.5/UG-387	
LO Connector	SMA Female	
IF Connector	SMA Female	
Size	97*28*24	mm

Absolute Maximum Ratings:

Parameter	Value
RF Input Power	0dBm
ESD sensitivity (HBm)	Class 0, passed 150V

Typical Performance Data:

Environmental Conditions:



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

Parameter	Min	Typ	Max	Units
Operating Temperature	0		+40	°C
Non-operating Temperature	-25		+65	°C
Relative humidity		95		%
Altitude	50,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

Ordering Information:

Part Number	Description	Revision
TLHM-110170-16-06	Spectrum Analyzer Harmonic Mixer RF:110-170 GHz,IF:DC-1.8GHz,16th,3 port design	Rev.1.1