

Model: TLLA6G18G-28-20
Low Noise Amplifier
6-18GHz, NF:2dB, Gain:28dB, P1dB:17dBm
Feature:

- Ultra Wide Band: 6-18GHz
- Gain: 28dB Typ
- Noise Figure: 2dB Max
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Electrical Specifications:

Parameter	Min	Typ	Max	Units
Frequency range	6-18			GHz
Gain		28		dB
Gain Flatness		±2.0		dB
Noise Figure			2.0	dB
Output P1dB		17		dBm
Input VSWR		2.0	2.2	:1
Output VSWR		2.0	2.2	:1
DC Voltage	+8	+12	+15	V DC
DC Supply Current		150		mA
Impedance	50			Ohms

Mechanical Specifications:

Parameter	Value	Units
Input /Output Connector	SMA Female/SMA Female	
DC Bias	Solder Pin	
Size	44.8*29.2*11	mm
Weight	55	g


Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	+15V
RF Input Power	15 dBm
ESD sensitivity (HBm)	Class 0, passed 150V


**Available 220V System
 Benchtop Amplifier**

Outline Drawing:

Unit: mm



*****Heat Sink Required During Operation**



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature	-45		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity		95		%
Altitude	50,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

Ordering Information:

Part Number	Description	Revision
TLLA6G18G-28-20	Low Noise Amplifier, 6-18GHz, Noise Figure:2dB, Gain:28 dB,P1dB:17dBm,12V DC,Without Heatsink	Rev.1.1
TLLA6G18G-28-20-HS	Low Noise Amplifier, 6-18GHz, Noise Figure:2dB, Gain:28 dB,P1dB:17dBm,12V DC,With Heatsink	Rev.1.1