



### Electrical & Environmental Characteristics

Impedance	50 Ω
Insulation Resistance	1000 MΩ
Operating Frequency	DC~40GHz
Dielectric Withstanding Voltage	325V
VSWR	≤1.25
Insertion Loss	≤0.05* $\sqrt{f\_GHz}$
Operating Temperature	- 55~+165°C

### Material & Coat-Plating

Inner Conductor	Beryllium Copper, Gold
Dielectric	PTFE
Body	Stainless Steel, Passivated
Coupling Nut	NA

No.	Model	X
1	TLSPM17LF08	有限擒纵

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model			
		PRODUCT SPEC	TLSPM17LF08 SMP male Flange Connector			
		APPLICATION SPEC	SIZE A4	GAGE CODE OT8L4	DRAWING NO	
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	CUSTOMER DRAWING		SHEET 1 OF 1	RVE 1