



Electrical & Environmental Characteristics

Impedance	50Ω
Insulation Resistance	≥5000MΩ
Operating Frequency	DC~40GHz
Dielectric Withstanding Voltage	325V
VSWR	≤1.25
Hermeticity	≤1.1013x10 ⁻³ Pa · cm ³ /sHe
Operating Temperature	- 55~+165℃

Material & Coat-Plating

Inner Conductor	4J29
Dielectric	Glass
Body	4J29

No.	Model	X
1	TLSPMY02	有限擒纵
2		

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model TLSPMY02 SSMP male, HERMETIC SEALED Adaptor			
		PRODUCT SPEC				
		APPLICATION SPEC				
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO	
		CUSTOMER DRAWING			SHEET1 OF 1	RVE 1