



No.	Model	Pin Size Ød
1	SSMA-KFD80809	0.23 [0.009]
2	SSMA-KFD80812	0.30 [0.012]
3	SSMA-KFD80815	0.38 [0.015]
4	SSMA-KFD80818	0.46 [0.018]
5	SSMA-KFD80820	0.51 [0.020]

Electrical & Environmental Characteristics

Impedance	50 Ω
Insulation Resistance	1000 MΩ
Operating Frequency	DC~40GHz
Dielectric Withstanding Voltage	750V
VSWR	≤1.2
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165°C

Material & Coat-Plating

Inner Conductor	Beryllium Copper, Gold
Dielectric	PTFE
Body	Stainless Steel, Passivated
Coupling Nut	NA

THIS DRAWING IS A CONTROLLED DOCUMENT

DWN

CHK

Suzhou Talent Microwave, Inc

Unit
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED

0 PLC ±0.25
1 PLC ±0.15
2 PLC ±0.12
3 PLC ±
3 PLC ±
ANGLES ±1°

APVD

PRODUCT SPEC

APPLICATION SPEC

Product Model

SSMA-KFD80815
SSMA Female Flange Connector

SIZE

A4

GAGE CODE

0T8L4

DRAWING NO

MATERIAL
SEE TABLE

FINISH
SEE TABLE

WEIGHT

CUSTOMER DRAWING

SHEET 1 OF 1

RVE 1