



Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000MΩ
Operating Frequency	DC-40GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.20
Insertion Loss	0.05* $\sqrt{f_{GHz}}$
Operating Temperature	- 55~+165℃
Inner Conductor	Beryllium copper gilding
Dielectric	PEI
Body	STAINLESS STEEL Passivtionof

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model NMD2.4F2.92F NMD2.4 Female 2.92 Female Connector			
		PRODUCT SPEC				
		APPLICATION SPEC				
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE OT8L4	DRAWING NO	
CUSTOMER DRAWING			SCALE 4: 1	SCALE 4: 1	SHEET 1 OF 1	RVE 1