

Low Noise Amplifier

2-8GHz/0.9dB NF/50dB Gain/13dBm P1dB

Model: TLLA2G8G-50-9

TLLA2G8G-50-9 is a low noise amplifier with a typical small signal gain of 50 dB and a nominal noise figure of 0.9 dB across the frequency range of 2 to 8 GHz. The DC power requirement for the amplifier is +5 V DC/80 mA. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 2-8GHz
- Gain: 50dB Typ
- Noise Figure: 0.9dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency range	2		8	GHz
Small Signal Gain		50		dB
Gain Flatness		±2.5		dB
Noise Figure		0.9	1	dB
Output P1dB		13		dBm
Output Psat		14		dBm
Input VSWR		1.8		:1
Output VSWR		1.8		:1
DC Voltage		+5	+8	V DC
DC Supply Current		80		mA
Impedance		50		Ohms

Mechanical Specifications:


Parameter	Value	Units
Input /Output Connector	SMA Female/SMA Female	
DC Bias	Solder Pin	
Size	44.8*29.2*11	mm

Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	+8 V
RF Input Power	+5 dBm
ESD sensitivity (HBm)	Class 0, passed 150V

Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Environmental Conditions:


Parameter	Min	Typ	Max	Units
Operating Temperature	-45		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

Ordering Information:

Base Number	Description	Revision
TLLA2G8G-50-9	Low Noise Amplifier, 2-8GHz, Noise Figure:0.9dB, Gain:50 dB,P1dB:13dBm,+5V DC,Without Heatsink	Rev.1.1
TLLA2G8G-50-9-HS	Low Noise Amplifier, 2-8GHz, Noise Figure:0.9dB, Gain:50 dB,P1dB:13dBm,+5V DC,With Heatsink	Rev.1.1

Typical Performance Data:

Gain&VSWR vs Frequency




Noise Figure vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:


Gain vs Output Power



P1dB vs Frequency




P3dB vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:

Psat vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.