

Coaxial Lowpass Filter

DC-4 GHz/2.92mm

Model: TLLF-DC-4G-K

TLLF-DC-4G-K is a coaxial lowpass filter with a passband frequency from DC to 4 GHz . The nominal insertion loss of the filter is 1.7 dB and the typical rejection is 40 dB.

Features:

- Passband Frequency Range DC to 4 GHz
- Low Insertion Loss

Applications:

- Instrumentations
- Test Labs
- Sub-assemblies

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Passband Frequency range	DC	4		GHz
Passband Insertion Loss			1.7	dB
Rejection	20@5.4GHz,40@6.7GHz			dB
Power Handling			1	W
Return Loss		18		dB
Impedance	50			Ohms

Environmental And Physical Characteristics:


Description	Parameter	Units
Operating Temperature	-55 To +125	°C
Storage Temperature	-65 to +150	°C
Connectors	2.92mm	

Outline Drawing:


Unit:mm



TLLF-DC-4G-K



TLLF-DC-4G-MM



TLLF-DC-4G-FF



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLLF-DC-4G-K	Coaxial Lowpass Filter, Passband frequency range: DC-4GHz, Passband Insertion Loss: 1.7dB, 2.92mm Male/2.92mm Female Coaxial Fixed Termination	Rev.1.1
TLLF-DC-4G-MM	Coaxial Lowpass Filter, Passband frequency range: DC-4GHz, Passband Insertion Loss: 1.7dB, 2.92mm Male Coaxial Fixed Termination	Rev.1.1
TLLF-DC-4G-FF	Coaxial Lowpass Filter, Passband frequency range: DC-4GHz, Passband Insertion Loss: 1.7dB, 2.92mm Female Coaxial Fixed Termination	Rev.1.1