

Coaxial Fixed Attenuator

2.92mm Male/DC-40GHz

Model:TAXXA2-2.92-40-M

TAXXA2-2.92-40-M is a 1~10/20/30/40 dB coaxial attenuator that is used in millimeterwave systems and operates from DC to 40 GHz.

Features:

- Operating Frequency DC to 40GHz
- Broadband Coverage
- Lost Cost

Applications:

- Test Lab
- Instrumentations
- System Integration


Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	DC		40	GHz
Attenuation Range		1~10 ± 0.7		dB
		20 ± 0.8		
		30 ± 0.8		
		40 ± 1		
VSWR			1.3	:1
Impedance		50		Ohms
RF Power Rating	2Watts Average at 25°C PEAK: 125 Watts(5 μs pulse width, 1% duty cycle)			

Envrionmental And Physical Characteristics:

Description	Parameter	Units
Operating Temerature	-55 To +125	°C
Body Material	Passivated stainless steel	
Connector Material	Passivated stainless steel	
Inner Conductor	Gold plated beryllium copper	
Insulators	PTFE, Virgin Electrical Grade	
Connectors	2.92mm Male	
Length	17.9	mm

Outline Drawing: Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description
TA01A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz,1±0.7dB Attenuation
TA02A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz,2±0.7dB Attenuation
TA03A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz,3±0.7dB Attenuation
TA04A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz,4±0.7dB Attenuation
TA05A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz,5±0.7dB Attenuation
TA06A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz,6±0.7dB Attenuation

Ordering Information:

Base Number	Description
TA07A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz, 7 ± 0.7 dB Attenuation
TA08A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz, 8 ± 0.7 dB Attenuation
TA09A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz, 9 ± 0.7 dB Attenuation
TA10A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz, 10 ± 0.7 dB Attenuation
TA20A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz, 20 ± 0.8 dB Attenuation
TA30A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz, 30 ± 0.8 dB Attenuation
TA40A2-2.92-40-M	Coaxial Fixed Attenuator, DC-40GHz, 40 ± 1 dB Attenuation