

E-Band Low Power Termination Load

60-90GHz/WR12/0.5W

Model: TLTT-6090-27-12

TLTT-6090-27-12 is a general purpose WR-12 millimeter waveguide termination. This waveguide termination will operate from 60 to 90 GHz. A Millimeter Waveguide Termination is a passive RF device specifically designed to prevent RF signals from reflecting back from open-ended or unused waveguide ports. Millimeter Waveguide Terminations dissipate RF energy by producing heat energy.

Features:

- Frequency range:60-90GHz
- High Return Loss
- Instrumentation Grade

Applications:

- Communication Systems
- Test Equipment

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
RF Frequency range	60		90	GHz
Return Loss		-35		dB
Power Handling			0.5	W

Mechanical Specifications:

Parameter	Value	Units
Operating Temperature	-55 To +125	°C
Storage Temperature	-55 To +125	°C
Connector	WR-12/UG-387/U	
Case Material	Copper	
Finish	Gold Plated	
Size	40.9*8.5	mm

Outline Drawing: Unit:mm

Regulatory Compliance:




Ordering Information:

Base Number	Description	Revision
TLTT-6090-27-12	E-Band Low Power Termination Load Return Loss:-35dB	Rev.1.1

Typical Performance Data:

Return Loss vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.