

Solid State High Power Amplifier Systems

6-18GHz/56dB Gain/55dBm Psat/220V AC

Model: TLP6G18G-56-55-BC

TLP6G18G-56-55-BC is a solid state high power amplifier systems provides high output power and high gain across the 6 to 18 GHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Frequency range: 6-18GHz
- Gain: 56dB Min
- Psat Output Power: 55dBm Min
- Protection: Over TEM, over voltage, over current, over VSWR protection
- 50 Ohm Matched Input / Output

Electrical Characteristics:

Parameter	Symbol	Min	Typ	Max	Units
Frequency range	BW	6		18	GHz
Power Gain	GP	56			dB
Gain flatness	Δ GL		± 4.5		dB
Output Psat	Psat	55			dBm
Spurious@Pout=55dBm	Spur			-60	dBc
Harmonics@Pout=55dBm	HAM			-15	dBc
Input VSWR	VSWRin			2	:1
AC Voltage	Vac		220		V AC
Power Consumption	Pdiss		3500		W
Impedance	I/O-IMP		50		Ohms

Mechanical Specifications:

Parameter	Value	Units
Input /Output Connector	N Female/WRD500*	
Forward/Reverse Coupling	SMA Female/ SMA Female	
Communication Connector	DB9/RJ45	
Front Panel LCD Screen Display	7 inch LCD Screen Display	
Size	19 Inch 5U*550	mm
Weight	≤ 45	Kg


*Note: WRD500 cannot be adapted to any coaxial interfaces.

Absolute Maximum Ratings:

Parameter	Value
RF Input Power	+5 dBm
ESD sensitivity (HBm)	Class 0, passed 150V

Outline Drawing:

Unit:mm



Key Features:

Parameter	Advantages
Control functions	1, Power setting on/off 2, Output power adjustment 3, Gain adjustment 4, Condition monitoring
Display functions	1, Output/reverse power 2, Fault informations
Protection functions	1, Over TEM 2, Over voltage 3, Over current 4, Over VSWR
Remote control	RS422/Ethernet
Cooling system	Built in Cooling system, forced air cooling

Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature*	-20		+40	°C
Non-operating Temperature*	-30		+50	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave, 3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

Ordering Information:

Base Number	Description	Revision
TLPA6G18G-56-55-BC	Solid State High Power Amplifier Systems 6-18GHz, Gain:56dB, Psat:55dBm, 220V AC, Built in Fan Cooling	Rev.1.0