

D-band Directional Waveguide Coupler

WR-6.5/30dB Coupling

Model: TC-110170-30-06

TC-110170-30-06 is a D-band, 3-port waveguide directional coupler that delivers a 30 dB nominal coupling level and 25 dB typical directivity across the full waveguide band from 110 to 170 GHz. The interfaces of the coupler are WR-6.5 waveguides with UG-387/U-M anti-cocking flanges.

Features:

- Operating Frequency 110 to 170 GHz
- Full Band Operation
- Low Insertion Loss
- Moderate Directivity

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Frequency Range	110		170	GHz
Insertion Loss		0.9		dB
Coupling		30		dB
Coupling Accuracy		±2		dB
Isolation		55		dB
Directivity		25		dB
Main Line VSWR		1.2		:1
Coupling Port VSWR		1.2		:1

Environmental And Physical Characteristics:

Description	Parameter	Units
Operating Temperature	-40 To +85	°C
Storage Temperature	-40 to +85	°C
Input/Output Connectors	WR-6.5/U-387/U	
Isolation/Coupling Port	WR-6.5/U-387/U	
Size	50*22*22	mm

Outline Drawing:

Unit:mm; Tolerance:±0.1mm



Ordering Information:

Base Number	Description	Revision
TC-110170-30-06	D-band Directional Waveguide Coupler,110-170GHz, Insertion Loss:0.9dB Typ, Coupling:30dB Typ,WR-6.5	Rev.1.0