Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Waveguide Bandpass Filter

WR-12/71-76GHz

Model: TLBF-071076-50-12

TLBF-071076-50-12 is a waveguide bandpass filter with a passband frequency from 71 to 76 GHz and a rejection frequency from DC to 67 GHz and 81 to 90 GHz. The maximum insertion loss of the filter is 2 dB and the minimum rejection is 50 dBc. The input and output port configuration offers an inline structure with WR-12 waveguides and UG-387/U-M anti-cocking flanges.

Features:

- Passband Frequency Range 71 to 76 GHz
- Lower Cost
- Low Insertion Loss
- High Rejection

Applications:

- Communicatin Systems
- Radar Systems
- Sub-assemblies

Electrical Characteristics:

Parameter		Min	Typ	Max	Units
Passband Frequency range		71		76	GHz
Passband Width			5		GHz
Input/Output VSWR			1.25		:1
Passband Insertion Loss				2	dB
Rejection	@DC-67 GHz	50			dBc
	@81-90 GHz	50			


Envrionmental And Physical Characteristics:

Parameter	Description	Units
Operating Temerature	-20 to +55	℃
Storage Temerature	-20 to +55	℃
Material	Aluminum	
Finish	Conductive Coating, Natural Finish	
Waveguide	WR-12/UG-387/U-M	

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLBF-071076-50-12	Waveguide Bandpass Filter,71-86GHz, Insertion Loss: 2dB, Rejection: 50dBc@DC-67GHz&81-90GHz,WR-12/UG-387/U-M	Rev.1.0