Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

High Power Directional Coupler

0.02-1GHz/50dB Coupling/N-K,SMA-K

Model: TDC-20M010-50N-500

TDC-20M010-50N-500 is a high power directional coupler that delivers a 50 dB nominal coupling level and 18 dB minimum directivity across the full frequency range from 0.02 to 1GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 0.02-1GHz
- Max Power: 500W(CW)
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	0.02		1	GHz
Insertion Loss(Excl coupling)			0.28	dB
Coupling		50±1		dB
Coupling Flatness			±1.8	dB
Directivity	18			dB
Main Line VSWR			1.3	:1
Power Handling			500	W
Impedance		50		Ohms

Mechanical Specifications:

Parameter	Value	Units
RF Connector	N-K(主线)、SMA-K（副线）	
Finish	Cavity: Silver plated Cover plate: Conductive oxidation	
Size	63.5*50*28	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm; Tolerance:±0.2mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature	-55		+85℃	
Relative humidity	100% RH at 35c, 95%RH at 40℃			%
Altitude	50,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

Ordering Information:

Base Number	Description	Revision
TDC-20M010-50N-500	High Power Directional Coupler 0.02-1 GHz, Coulping:50dB, N-K(主线)、SMA-K（副线）	Rev.1.0