

Coaxial Band-pass Filter

13.5-14 GHz/SMA Female

Model: TLBF-13G5-14G-S

TLBF-13G5-14G-S is a coaxial band-pass filter with a passband frequency from 13.5 to 14 GHz and a rejection frequencies @13.25 GHz and 14.25GHz. The maximum insertion loss of the filter is 1.0 dB and the typical rejection is 40 dB.

Features:

- Passband Frequency Range 13.5 to 14 GHz
- Low Insertion Loss
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations

电气特性 Electrical Characteristics:


参数 Parameter	Min	Typ	Max	单位 Units
通带频率范围 Passband Frequency range	13.5		14	GHz
通带插损 Passband Insertion Loss			1.0	dB
带外抑制 Rejection	≥40dBc@13.25&14.25GHz			dB
耐受功率 Power Handling			10	W
驻波 VSWR			1.5	:1
阻抗 Impedance	50			Ohms

环境和机械特性 Envriionmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
操作温度 Operating Temperature	-55 To +85	°C
接口 Connectors	SMA Female	
重量 Weight	/	g

外形图 Outline Drawing:

Unit:mm




ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLBF-13G5-14G-S	Coaxial Band-pass Filter, Passband frequency range: 13.5-14GHz, Passband Insertion Loss: 1.0dB, SMA Female	Rev.1.0

典型曲线 Typical Performance Data:



7/18/2025, 2:23 PM

Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.