泰莱微波 Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Cryogenic Coax Attenuators

DC-18GHz/2W/SSMP/Non-Magnetic

Model:TAXXA2-SSMP-18-Cryo

TAXXA2-SSMP-18-Cryo is working to customize and optimize fixed attenuators for use in cryogenic cooling systems to support quantum computing. Eliminating thermal noise in a quantum computing installation demands a high degree of innovation and reliability. TAXXA2-SSMP-18-Cryo's experience delivering custom components for use in harsh environments and high reliability requirements,is the foundation supporting our work in cryogenic technology.

Features:

- Frequency: DC to 18 GHz
- Max Power: 2W
- Capable of operation at 10 mK
- Non-Magnetic
- 50 Ohm Matched Input / Output

Applications:

- Dilution refrigerators/Cryogenic devices
- Quantum Computing

电气特性 Electrical Characteristics:

参数 Parameter		Min	Typ	Max	单位 Units
频率范围 Frequency range			DC-18		GHz
标准衰减值 Standard dB Values			0~10/12/15/20/30		dB
衰减精度 Attenuation Accuracy	0dB			+0/-0.4	dB
	1-6dB			±0.6	
	10-20dB			±1.2	
	30dB			±1.5	
驻波 VSWR	DC-4GHz		1.1		:1
	4-12.4GHz		1.15		
	12.4-18GHz		1.25		
输入功率 Input Power				2	W
阻抗 Impedance			50		Ohms

泰莱微波
Talent Microwave


Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

机械特性 Mechanical Specifications:

描述 Description	参数 Parameter	单位 Units
输入/输出接口 Input /Output Connector	SSMP Male/SSMP Female	
外壳材质 Case Material	BeCu	
表面 Finish	Gold Plated	
电阻材料 Resistor Material	Proprietary Thin Film	

外形图 Outline Drawing:

Unit:mm



温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	10mK		+85	℃
存储温度 Non-operating Temperature	-55		+125	℃
相对湿度 Relative humidity	100% RH at 35c, 95%RH at 40℃			%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

订货信息 Ordering Information:

标准型号 Base Number		标准衰减值 Standard dB Values	版本号 Revision
SSMP Male/SSMP Female	SSMP Male/SSMP Male		
TA00A2-SSMP-18-Cryo-MF	TA00A2-SSMP-18-Cryo-MM	0dB	Rev.1.1
TA01A2-SSMP-18-Cryo-MF	TA01A2-SSMP-18-Cryo-MM	1dB	Rev.1.1
TA02A2-SSMP-18-Cryo-MF	TA02A2-SSMP-18-Cryo-MM	2dB	Rev.1.1
TA03A2-SSMP-18-Cryo-MF	TA03A2-SSMP-18-Cryo-MM	3dB	Rev.1.1
TA04A2-SSMP-18-Cryo-MF	TA04A2-SSMP-18-Cryo-MM	4dB	Rev.1.1
TA05A2-SSMP-18-Cryo-MF	TA05A2-SSMP-18-Cryo-MM	5dB	Rev.1.1
TA06A2-SSMP-18-Cryo-MF	TA06A2-SSMP-18-Cryo-MM	6dB	Rev.1.1
TA07A2-SSMP-18-Cryo-MF	TA07A2-SSMP-18-Cryo-MM	7dB	Rev.1.1
TA08A2-SSMP-18-Cryo-MF	TA08A2-SSMP-18-Cryo-MM	8dB	Rev.1.1
TA09A2-SSMP-18-Cryo-MF	TA09A2-SSMP-18-Cryo-MM	9dB	Rev.1.1
TA10A2-SSMP-18-Cryo-MF	TA10A2-SSMP-18-Cryo-MM	10dB	Rev.1.1
TA12A2-SSMP-18-Cryo-MF	TA12A2-SSMP-18-Cryo-MM	12dB	Rev.1.1
TA15A2-SSMP-18-Cryo-MF	TA15A2-SSMP-18-Cryo-MM	15dB	Rev.1.1
TA20A2-SSMP-18-Cryo-MF	TA20A2-SSMP-18-Cryo-MM	20dB	Rev.1.1
TA30A2-SSMP-18-Cryo-MF	TA30A2-SSMP-18-Cryo-MM	30dB	Rev.1.1