泰莱微波 Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

High Power Dual-Directional Coupler

0.6-2.7GHz/50dB Coupling/N Female Model: TDC-006027-50N-800

TDC-006027-50N-800 is a high power dual-directional coupler that delivers a 50 dB nominal coupling level and 20 dB minimum directivity across the full frequency range from 0.6 to 2.7GHz. It is a four-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 0.6-2.7GHz
- Max Power: 800W
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

电气特性 Electrical Characteristics:


参数 Parameter	Min	Typ	Max	单位 Units
工作频率 Frequency Range	0.6		2.7	GHz
插入损耗 Insertion Loss(Excl coupling)			0.3	dB
耦合度 Coupling		50±1.2		dB
方向性 Directivity	20			dB
主线驻波 Main Line VSWR			1.3	:1
耐功率 Power Handling			800	W
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
操作温度 Operating Temperature	-45 to +85	℃
RF接口 RF Connector	N Female	
耦合接口 Coupling Connector	SMA Female	
尺寸 Size	85*44*26	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

外形图 Outline Drawing: Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TDC-006027-50N-800	High Power Dual-Directional Coupler 0.6-2.7GHz, Coulping:50dB, N/SMA Female	Rev.1.0