泰莱微波 Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Low Noise Amplifier

0.1-3GHz/1.0dB NF/28dB Gain/17dBm P1dB Model: TLLA0.1G3G-28-10

TLLA0.1G3G-28-10 is a low noise amplifier with a minimum small signal gain of 28 dB and a maximum noise figure of 1.0dB across the frequency range of 0.1 to 3 GHz. The DC power requirement for the amplifier is +12 V DC/70 mA. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 0.1-3 GHz
- Gain: 28dB Min
- Noise Figure: 1.0dB Max
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.1		3	GHz
小信号增益 Small Signal Gain	28	29		dB
噪声系数 Noise Figure		0.8	1.0	dB
线性输出功率 Output P1dB	14	17		dBm
饱和输出功率 Output Psat		18		dBm
输入驻波 Input VSWR		1.8		:1
输出驻波 Output VSWR		1.4		:1
直流电压 DC Voltage	+8	+12	+15	V DC
直流电流 DC Supply Current		70		mA
阻抗 Impedance		50		Ohms

*Performance may degrade below 300 MHz. Please refer to below typical test plots

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	20*28*10	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

绝对最大值 Absolute Maximum Ratings:


参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15 V
输入功率 RF Input Power	+15 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



Simple 220V System
Available SAC option

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm





ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

***Heat Sink Required During Operation

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-40		+60	℃
存储温度 Non-operating Temperature	-55		+125	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLLA0.1G3G-28-10	Low Noise Amplifier, 0.1-3GHz, Noise Figure:1.0dB, Gain:28 dB,P1dB:17dBm,+12V DC,Without Heatsink	Rev.1.1
TLLA0.1G3G-28-10-HS	Low Noise Amplifier, 0.1-3GHz, Noise Figure:1.0dB, Gain:28 dB,P1dB:17dBm,+12V DC,With Heatsink	Rev.1.1


典型曲线 Typical Performance Data:

Gain&VSWR vs Frequency



Frequency(GHz)

Noise Figure vs Frequency





Frequency(GHz)


Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

典型曲线 Typical Performance Data:







Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.