

## Low Noise Amplifier

6-34GHz/3.5dB NF/32dB Gain/14dBm P1dB

Model: TLLA6G34G-32-35

TLLA6G34G-32-35 is a low noise amplifier with a typical small signal gain of 32 dB and a nominal noise figure of 3.5 dB across the frequency range of 6 to 34 GHz. The DC power requirement for the amplifier is +12 V DC/280 mA. The input and output port configuration offers coax adapter structure with 2.92mm female.

### Features:

- Frequency range: 6-34GHz
- Gain: 32dB Typ
- Noise Figure: 3.5dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

### Applications:

- Communication systems

## 电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	6		34	GHz
小信号增益 Small Signal Gain	30	32		dB
增益平坦度 Gain Flatness		±2.5		dB
噪声系数 Noise Figure		3.5		dB
线性输出功率 Output P1dB	13	14		dBm
饱和输出功率 Output Psat		15		dBm
输入驻波 Input VSWR		1.6		:1
输出驻波 Output VSWR		1.6		:1
直流电压 DC Voltage	+8	+12	+13	V DC
直流电流 DC Supply Current		280		mA
阻抗 Impedance		50		Ohms

## 机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/2.92mmFemale	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	44*36*12	mm


## 绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+13V
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



## 外形图 Outline Drawing:

Unit:mm



## \*\*\*Heat Sink Required During Operation



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

## 温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

## 订货信息 Ordering Information:


标准型号 Base Number	描述 Description	版本号 Revision
TLLA6G34G-32-35	Low Noise Amplifier, 6-34GHz, Noise Figure:3.5dB, Gain:32dB,P1dB:14dBm,+12V DC,Without Heatsink	Rev.1.1
TLLA6G34G-32-35-HS	Low Noise Amplifier, 6-34GHz, Noise Figure:3.5dB, Gain:32dB,P1dB:14dBm,+12V DC,With Heatsink	Rev.1.1

## 典型曲线 Typical Performance Data:

### Gain&VSWR vs Frequency






### Noise Figure vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

**典型曲线 Typical Performance Data:**



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.