

Power Amplifier

0.4-150MHz/30dB Gain/30dBm P1dB

Model: TLPA0.4M150M-30-30

TLPA0.4M150M-30-30 is a power amplifier with a typical small signal gain of 30 dB and a minimum P1dB of 30 dBm across the frequency range of 0.4 to 150 MHz. The DC power requirement for the amplifier is +24 VDC/0.5 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 0.4-150MHz
- Gain: 30dB Typ
- Output Power P1dB: 30dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.4		150	MHz
小信号增益 Small Signal Gain	27	30		dB
增益平坦度 Gain Flatness		±0.5	±1	dB
线性输出功率 Output P1dB	30	31		dBm
三阶互调 Output IP3		38		dBm
输入驻波 Input VSWR			2.0	:1
输出驻波 Output VSWR			2.0	:1
直流电压 DC Voltage		+24	+28	V DC
直流电流 DC Supply Current		0.5	0.6	A
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	76*64*40(With heatsink)	mm
重量 Weight	200	g


绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+28 V
输入功率 RF Input Power	+10 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



外形图 Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	20g,11ms,saw-tooth			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA0.4M150M-30-30	Power amplifier 0.4-150MHz, Gain:30dB,P1dB:30dBm,+24V DC,Without Heatsink	Rev.1.1
TLPA0.4M150M-30-30-HS	Power amplifier 0.4-150MHz, Gain:30dB,P1dB:30dBm,+24V DC,With Heatsink	Rev.1.1

典型曲线 Typical Performance Data:


Input VSWR vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Output VSWR vs Frequency



Small Signal Gain vs Frequency




Gain vs Output Power




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


PndB vs Frequency



Psat vs Frequency




2nd Harmonics vs Output Power




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:

3rd Harmonics vs Output Power



4th Harmonics vs Output Power



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.