

Solid State High Power Amplifier Systems

0.1-400MHz/53dB Gain/200W Psat/220V AC

Model: TLPA0.1M400M-53-53-BC

TLPA0.1M400M-53-53-BC is a solid state high power amplifier systems provides high output power and high gain across the 0.1 to 400MHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Frequency range: 0.1-400MHz
- Gain: 53dB Min
- Psat Output Power: 200W Min
- Protection: Over TEM, over voltage, over current, over VSWR protection
- 50 Ohm Matched Input / Output

电气特性 Electrical Characteristics:

参数 Parameter	代码 Symbol	Min	Typ	Max	单位 Units
频率范围 Frequency range	BW	0.1-400			MHz
功率增益 Power Gain	GP	53			dB
增益平坦度 Gain flatness	Δ GL			± 3.5	dB
线性输出功率 Output P1dB	P1dB	150			W
饱和输出功率 Output Psat	Psat	200			W
杂散 Spurious@Pout=	Spur			-50	dBc
谐波 Harmonics@Pout=	HAM			-15	dBc
输入驻波 Input VSWR	VSWRin			2.0	:1
交流电压 AC Voltage	Vac		220		V AC
功耗 Power Consumption	Pdiss			800	W
阻抗 Impedance	I/O-IMP	50			Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	N Female/N Female	
正向/反向耦合 Forward/Reverse Coupling	N Female/N Female	
控制接口 Control Connector	GPIB/Ethernet	
尺寸 Size	19 Inch 4U	mm
重量 Weight	≤ 25	Kg

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	0 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



主要功能 Key Features:

参数 Parameter	特点 Advantages
控制功能 Control functions	1, Power setting On/Off 2, Gain adjustment (additional fees are required)
内置保护功能 Protection functions	1, Over TEM ($\leq 60^{\circ}\text{C}$) 2, Over voltage 3, Over current 4, Over VSWR ($\leq 5:1$) 5, Over excited ($< 200\text{W}$)
监控和控制 Remote control	RS422/Ethernet
冷却系统 Cooling system	Built in Cooling system, forced air cooling

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+40	$^{\circ}\text{C}$
存储温度 Non-operating Temperature*	-30		+50	$^{\circ}\text{C}$
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration (MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock (non operating)	20G for 11msc half sin wave, 3 axis both directions			


*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:


标准型号 Base Number	描述 Description	版本号 Revision
TLPA0.1M400M-53-53-BC	Solid State High Power Amplifier Systems 0.1-400MHz, Gain:53dB, Psat:200W, 220V AC, Built in Fan Cooling	Rev.1.1

典型曲线 Typical Performance Data:

Gain&P1dB&Psat vs Frequency



Input VSWR vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.