

Power Amplifier

17-40GHz/35dB Gain/30dBm Psat

Model: TLPA17G40G-35-29

TLPA17G40G-35-29 is a power amplifier with a typical small signal gain of 35 dB and a nominal Psat of 30 dBm across the frequency range of 17 to 40 GHz. The DC power requirement for the amplifier is +12 VDC/700 mA. The input and output port configuration offers coax adapter structure with 2.92mm female.

Features:

- Frequency range: 17-40GHz
- Gain: 35dB Typ
- Output Power Psat: 30dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	17		40	GHz
小信号增益 Small Signal Gain	33	35	38	dB
线性输出功率 Output P1dB	27.5	29		dBm
饱和输出功率 Output Psat	28.5	30		dBm
输入驻波 Input VSWR		1.8		:1
输出驻波 Output VSWR		1.8		:1
直流电压 DC Voltage		12		V DC
直流电流 DC Supply Current		700		mA
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/2.92mm Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	50*65*14(Without heatsink) 50*111*64(With heatsink)	mm

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+8 V
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm




*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

外形图 Outline Drawing:

Unit:mm



温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA17G40G-35-29	Power amplifier 17-40GHz, Gain:35dB,Psat:30dBm,+12V DC,Without Heatsink	Rev.1.0
TLPA17G40G-35-29-HS	Power amplifier 17-40GHz, Gain:35dB,Psat:30dBm,+12V DC,With Heatsink	Rev.1.0