

Coaxial High-pass Filter

1-18 GHz/SMA Female

Model: TLHF-1G-18G-X

TLHF-1G-18G-X is a coaxial High-pass filter with a passband frequency from 1 to 18 GHz and a rejection frequency from DC to 0.8 GHz. The maximum insertion loss is 1.5 dB and the minimum rejection is 45 dB.

Features:

- Passband Frequency Range 1 to 18GHz
- Low Insertion Loss

Applications:

- Instrumentations
- Test Labs
- Sub-assemblies

电气特性 Electrical Characteristics:


参数 Parameter	Min	Typ	Max	单位 Units
带通频率范围 Passband Frequency range	1		18	GHz
带通插损 Pass Band Insertion Loss			1.5	dB
带内波动 Pass band Ripple			1.2	dB
耐受功率 Power Handling			10	W
驻波 VSWR			1.8	:1
带外抑制 Rejection	>45dB@dc-0.8Ghz			
阻抗 Impedance	50			Ohms

环境和机械特性 Envirionmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
操作温度 Operating Temerature	-40 To +85	°C
接口 Connectors	SMA Female	

外形图 Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLHF-1G-18G-X	Coaxial High-pass Filter, Passband frequency range: 1-18GHz, Passband Insertion Loss: 1.5dB, SMA Female	Rev.1.1