

Power Amplifier

2-18GHz/30dB Gain/40dBm Psat

Model: TLPA2G18G-30-40

TLPA2G18G-30-40 is a power amplifier with typical small signal gain of 30 dB and a minimum Psat of 40 dBm across the frequency range of 2 to 18 GHz. The DC power requirement for the amplifier is +28 VDC/2.3 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 2-18GHz
- Gain: 30dB Typ
- Output Power Psat: 40dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	2		18	GHz
小信号增益 Small signal Gain		30		dB
增益平坦度 Gain Flatness		±4		dB
饱和输出功率 Output Psat	40			dBm
杂散 Spurious@Pout=40dBm			-50	dBc
二次谐波 2nd Harmonic@Pout=40dBm		-10		dBc
输入驻波 Input VSWR		2		:1
直流电压 DC Voltage		28		V DC
直流电流 DC Supply Current		2.3		A
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	60*60*11.5(Without heatsink) 150*127*74.5(With heatsink)	mm


绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+29 V
输入功率 RF Input Power	+20 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+50	°C
存储温度 Non-operating Temperature*	-50		+60	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA2G18G-30-40	Power amplifier 2-18GHz, Gain:30dB,Psat:40dBm,+28V DC,With Heatsink	Rev.1.0