

J-Band VNA Frequency Extender

220-330GHz/WR-3.4

Model: TLTE-220330-N3/TLRE-220330

TLTE-220330-N3/TLRE-170260 frequency extenders are a dedicated Test & Measurement solution for extending the range of your Vector Network Analyzer (VNA) to 220-330 GHz.

Features:

- Frequency range: 220-330 GHz
- Port Output Power: -3dBm Typ
- Dynamic Range @10Hz BW: 100dB Typ
- Unconditional stability

Applications:

- VNA Frequency Extension
- Antenna measurements
- Material characterisation

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	220		330	GHz
测试端口输出功率 Test Port Output Power		-3		dBm
动态范围 Dynamic Range @10Hz BW		100		dB
射频输入频率 RF Input Frequency	12.22		18.33	GHz
射频输入功率 RF Input Power	3	5	7	dBm
RF倍频次数 RF Multiplication Factor	18			
本振输入频率 LO Input Frequency	9.16		13.75	GHz
本振输入功率 LO Input Power	3	5	7	dBm
LO倍频次数 LO Multiplication Factor	24			
接收端变频损耗 Conversion Loss of Receiver		15		dB
中频频率范围 IF Frequency Range	1		1000	MHz
幅度稳定度 Amplitude Stability @300Hz BW		±0.3		dB
相位稳定度 Phase Stability @300Hz BW		±6		°


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value
RF/LO输入接口 RF/LO Input Connector	SMA Female
MEA/REF IF输出接口 MEA/REF IF Output Connector	SMA Female
测试端口 Test Port Connector	WR-3.4/UG-387/U
供电 Power Supply Pin	FGG 0B 4 Core

绝对最大值 Absolute Maximum Ratings :

描述 Description	参数 Parameter	单位 Units
RF/LO端损坏等级(发射参考模块) RF/LO Port Damage Level (Transmit Extender)	+10	dBm
RF端损坏等级(接收模块) RF Port Damage Level (Receiver Extender)	0	dBm
LO端损坏等级(接收模块) LO Port Damage Level (Receiver Extender)	+10	dBm
供电偏置 Supply Bias Voltage	+240 V AC	
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V	

原理框图 Block Diagrams:



环境和物理特性 Envriomental And Physical

描述 Description	参数 Parameter	单位 Units
操作温度 Operating Temerature	0 to +45	°C
存储温度 Storage Temerature	-55 to +125	°C
材质 Material	Aluminum	
表面处理 Finish	Gray spray paint	

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号 Revision
TLTE-220330-N3	J-band VNA Frequency Extender,220-330GHz,Output Power:-3dBm typ, Dynamic Range: 100dB typ.,Magnitude Stability @300Hz BW:±0.3dB,Phase Stability @300Hz BW:±6°	Rev.1.1
TLRE-220330	J-band Receiver Module,220-330GHz,Conversion Loss: 15dB typ.	Rev.1.1

随货配件 Components Included:

标准型号 Part Number	描述 Description	数量 Quantity
S1-SMAMSMAM-1.2m	COAXIAL CABLE ASSEMBLY	4 PCS
TLACTDC-22012	AC-to-DC Power Adapter	1 PCS

Notes:

1. Dimensions and specifications may be changed without prior notice.
2. Standard Warranty:three years.