泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coaxial Isolator

6-18GHz/30W,Power Handling

Model: TLI6G18G-20W

The TLI6G18G-20W is a coaxial isolator designed to operate from 6GHz to 18GHz. The coaxial isolator offers minimum 12dB isolation and 1.65:1 maximum VSWR. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 6-18GHz
- Isolation: 12dB min
- Insertion Loss: 1dB Max
- 50 Ohm Matched Input / Output

Applications:

- Communication Systems
- Laboratory test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	6		18	GHz
插损 Insertion Loss@25℃			1	dB
插损 Insertion Loss@-30~+70℃			1.5	dB
隔离度 Isolation@25℃	12			dB
隔离度 Isolation@-30~+70℃	11			dB
驻波 VSWR@25℃			1.65	:1
驻波 VSWR@-30~+70℃			1.7	:1
耐功率 Power handling		20		W
反射功率 Reverse Power		20		W
方向 Direction	1→2			
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
操作温度 Operating Temerature	-30 To +70	℃
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
尺寸 Size	21*28.5*15	mm


Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	+43 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLI6G18G-20W	Coaxial Isolator, 6-18GHz, Isolation: 12dB Min	Rev.1.0