



### Electrical & Environmental Characteristics

Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~18GHz
Dielectric Withstanding Voltage	750V
VSWR	≤1.15@18G
Insertion Loss	≤0.06*v(f(GHz)) dB
Operating Temperature	- 55~+125℃

### Material & Coat-Plating

Inner Conductor	Be-Cu, Gold Plated
Dielectric	PTFE
Body	Stainless Steel,Passivated
Coupling Nut	Stainless Steel,Passivated

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave,Inc		
		CHK			
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model  SSMA/SMA-KJ SSMA Female To SMA male Straight Adaptor		
		PRODUCT SPEC			
		APPLICATION SPEC	SIZE A4	GAGE CODE 0T8L4	DRAWING NO
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	CUSTOMER DRAWING		
					SHEET 1 OF 1 RVE 1