

Model: TMPA-085135-1622-08
Power Amplifier
85-135GHz, Psat:22 dBm, Gain:17 dB
Feature:

- Frequency Range: 85-135 GHz
- Gain:17 dBm Typ
- Output Power Psat: 22 dBm Typ
- Good Power and Gain Flatness

电气特性 Electrical:

参数Parameter	Min.	Typ.	Max.	单位Units
频率范围 Frequency range	85-135			GHz
增益 Gain		17		dB
饱和输出功率Psat		22		dBm
输入功率 Input Power		12		dBm
输入驻波 Input VSWR		2.0		:1
输出驻波 Output VSWR		2.0		:1
直流电压 DC Voltage		9		V DC
直流电流 DC Supply Current		1500		mA

机械特性 Mechanical :

参数Parameter	指标 Value	单位 Units
输入输出接口 Input /Output Connector	WR-08/UG-387/U	
直流偏置 Bias	Solder Pin	
尺寸 Size	30*50*22	mm
重量 Weight	/	g



绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	TBD
输入功率 RF INPUT POWER	12 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V


 Available 220V System
 Benchtop Amplifier

外形尺寸 Outline Drawing:

Unit: mm(Inches)



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:

参数Parameter	Min.	Typ.	Max.	单位Units
操作温度 Operating Temperature	0		+50	°C
存储温度 Non-operating Temperature	-45		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TMPA-085135-1622-08	Power Amplifier 85-135 GHz, Psat:22dBm, Gain:17 dBm,WR-08	Rev.1.1