

Model: TMLA-210260-1970-04
**Low Noise Amplifier, G-Band
 210-260GHz, NF:7.0 dB, Gain:19 dB**
Feature:

- Ultra Wide Band: 210-260 GHz
- Gain: 19dB Typ
- Noise Figure: 7.0dB Typ
- Unconditional stability

电气特性 Electrical:

参数Parameter	Min.	Typ.	Max.	单位Units
频率范围 Frequency range	210		260	GHz
增益 Gain		19		dB
噪声系数 Noise Figure		7.0		dB
输入驻波 Input VSWR		2.5		: 1
输出驻波 Output VSWR		3.5		: 1
直流电压 DC Voltage		5		V DC
直流供电 DC power supply		43		mA

机械特性 Mechanical :

参数Parameter	指标 Value
输入接口 Input Connector	WR-04/ UG-387/U
输出接口 Output Connecto	WR-04/ UG-387/U
供电引脚 Power Supply Pin	Solder Pin
尺寸 Size	35*30*30mm


绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+5V
输入功率 RF INPUT POWER	TBD
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V


 Available 220V System
 Benchtop Amplifier

外形尺寸 Outline Drawing:

Unit: mm(Inches)



温度环境 Environmental Conditions:

参数Parameter	Min.	Typ.	Max.	单位Units
操作温度 Operating Temperature	-55		+85	°C
存储温度 Non-operating Temperature	-45		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TMLA-210260-1970-04	Low Noise Amplifier,210-260GHz, Noise Figure:7.0dB, Gain:19dB,5V DC,WR-08	Rev.1.1

典型曲线 Typical Performance Data:

