

Model:TMAM-071081-0625-12
**Active Frequency Multiplier,
 X6,71-81GHz, 25dBm Output Power**
Feature:

- Output Frequency:71-81GHz
- Output Power :25 dBm Typ
- Low power consumption

电气特性 Electrical Specifications:

参数 Parameter	Min	Typ	Max	单位 Units
输出频率 Output Frequency	71		81	GHz
输出功率 Output Power	23	25		dBm
输入频率 Input Frequency	11.833		13.5	GHz
输入功率 Input Power	0	3	5	dBm
倍频次数 Multiply Factor		6		Time
供电电压 DC Voltage	5.5			V
供电电流 DC Supply Current		1450		mA

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输出接口 Output Connector	WR-12/UG-387/U	
输入接口 Input Connector	SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	54*35*20	mm


绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	5.5V
输入功率 RF Input Power	5dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V


**Available 220V System
 Benchtop Amplifier**

外形尺寸 Outline Drawing:

Unit: mm



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	°C
存储温度 Non-operating Temperature	-45		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude		50,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号 Revision
TMAM-071081-0625-12	Active Multiplier,X6,71-81GHz, Output Power:25dBm,WR-12/UG-387/U,SMA Female	Rev.1.1