

Model: TMPA-090098-3023-10

Power Amplifier

90-98 GHz, Gain:30 dB,Psat:23 dBm

Feature:

- Frequency Range:90-98 GHz
- Gain:30 dB Typ
- Output Power Psat:23 dBm Typ
- Good Power and Gain Flatness

Electrical Specifications:

Parameter	Min	Typ	Max	Units
Frequency range	90-98			GHz
Gain		30		dB
Output Psat		23		dBm
Input VSWR		2.5		:1
DC Voltage		16		V DC
DC Supply Current		310		mA

Mechanical Specifications:

Parameter	Value	Units
Input /Output Connector	WR-10/UG-387/U	
DC Bias	Solder Pin	
Size	45*44*24(Without Heatsink) 45*56*42(With Heatsink)	mm
Weight	/	g

Absolute Maximum Ratings:


Parameter	Value
Supply Bias Voltage	TBD
RF Input Power	TBD
ESD sensitivity (HBm)	Class 0, passed 150V



**Available 220V System
Benchtop Amplifier**

Outline Drawing:

Unit: mm(Inches)



Environmental Conditions:



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

Parameter	Min	Typ	Max	Units
Operating Temperature	-10		+50	°C
Non-operating Temperature	-45		+125	°C
Relative humidity		95		%
Altitude	50,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

Ordering Information:

Part Number	Description	Revision
TMPA-090098-3023-10	Power Amplifier,90-98 GHz, Gain:30 dB Typ,Psat:23 dBm Typ,16V DC,WR-10	Rev.1.1