

**Model: TMLA-195230-2568-04**
**Low Noise Amplifier**  
**195-230GHz, NF:6.8 dB, Gain:22dB**
**Feature:**

- Ultra Wide Band: 195-230 GHz
- Gain: 22dB Typ
- Noise Figure:6.8dB Typ
- Unconditional stability

**电气特性 Electrical Specifications:**

参数Parameter	Min	Typ	Max	单位Units
频率范围 Frequency range	195		230	GHz
增益 Gain		22		dB
噪声系数 Noise Figure		6.8		dB
输入驻波 Input VSWR		2		:1
输出驻波 Output VSWR		2.5		:1
直流电压 DC Voltage		+5		V DC
直流供电 DC power supply		40		mA

**机械特性 Mechanical Specifications:**

参数Parameter	指标 Value	单位Units
输入接口 Input Connector	WR-04/ UG-387/U	
输出接口 Output Connector	WR-04/ UG-387/U	
供电引脚 Power Supply Pin	Solder Pin	
尺寸 Size	/	mm


**绝对最大值 Absolute Maximum Ratings:**

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+5 V
输入功率 RF Input Power	TBD
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V


**Available 220V System  
 Benchtop Amplifier**

外形尺寸 Outline Drawing:

Unit: Inches(mm)



温度环境 Environmental Conditions:


参数Parameter	Min	Typ	Max	单位Units
操作温度 Operating Temperature	-55		+85	°C
存储温度 Non-operating Temperature	-45		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TMLA-195230-2568-04	Low Noise Amplifier,195-230GHz, Noise Figure:6.8dB, Gain:22dB,+5V DC,WR-04	Rev.1.1

典型曲线 Typical Performance Data:

Input Return Loss vs Frequency



Gain vs Frequency

