

Model: TLLA18G40G-30-60
Low Noise Amplifier
18-40GHz, NF:6.0dB, Gain:30dB, P1dB:25dBm
Feature:

- Ultra Wide Band: 18-40GHz
- Gain: 30dB Typ
- Noise Figure: 6.0dB Max
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

电气特性 Electrical Specifications:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	18-40			GHz
增益 Gain		30		dB
增益平坦度 Gain Flatness		±4		dB
噪声系数 Noise Figure		3.5	6	dB
线性输出功率 Output P1dB	25			dBm
杂散 Spurious			-60	dBc
谐波 Harmonic			-15	dBc
输入驻波 Input VSWR		2		:1
直流电压 DC Voltage		12		V DC
功耗 Power Consumption			7	W
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/2.92mm Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	/	mm
重量 Weight	≤200	g


绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+12V
输入功率 RF Input Power	5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V


**Available 220V System
Benchtop Amplifier**

外形尺寸 Outline Drawing:

Unit: mm(inches)



*****Heat Sink Required During Operation**



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-40		+60	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号 Revision
TLLA18G40G-30-60	Low Noise Amplifier, 18-40GHz, Noise Figure:6.0dB, Gain:30 dB,P1dB:25dBm,+12V DC,Without Heatsink	Rev.1.1
TLLA18G40G-30-60-HS	Low Noise Amplifier, 18-40GHz, Noise Figure:6.0dB, Gain:30 dB,P1dB:25dBm,+12V DC,With Heatsink	Rev.1.1