



Electrical & Environmental Characteristics

Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC~90GHz
Dielectric Withstanding Voltage	500V
VSWR	≤1.40
Insertion Loss	≤0.60dB
Operating Temperature	- 55~+125℃
Material & Coat-Plating	
Inner Conductor	BE-CU, Gold Plated
Dielectric	PEI
Body	Stainless steel, Passivation
Nut	Stainless steel, Passivation

THIS DRAWING IS A CONTROLLED DOCUMENT

DWN

CHK

Suzhou Talent Microwave, Inc

Unit
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED
 0 PLC ±0.25
 1 PLC ±0.15
 2 PLC ±0.12
 3 PLC ±
 3 PLC ±
 ANGLES ±1°

APVD

PRODUCT SPEC

APPLICATION SPEC

Product Model

 1.35/1.0-KJ
 1.35mm Female to 1.0mm Male Adaptor

MATERIAL
SEE TABLE

FINISH
SEE TABLE

WEIGHT

SIZE

A4
GAGE CODE
0T8L4

DRAWING NO

CUSTOMER DRAWING

SHEET 1 OF 1

RVE 1