



No.	Model	D(Diameter)	L(Length)
1	2.92-KFD51309-127	0.23 [0.009]	0.5 [0.020]
2	2.92-KFD51309-039	0.23 [0.009]	1 [0.039]
3	2.92-KFD51312-011	0.30 [0.012]	0.3 [0.012]
4	2.92-KFD51312-019	0.30 [0.012]	0.5 [0.020]
5	2.92-KFD51312-059	0.30 [0.012]	1.5 [0.059]
6	2.92-KFD51312-079	0.30 [0.012]	2 [0.079]
7	2.92-KFD51312	0.30 [0.012]	7 [0.276]
8	2.92-KFD51312-354	0.30 [0.012]	9 [0.354]
9	2.92-KFD51312-472	0.30 [0.012]	12 [0.472]
10	2.92-KFD51312-50	0.30 [0.012]	12.7 [0.500]
11	2.92-KFD51317-269	0.44 [0.017]	6.84 [0.269]
12	2.92-KFD51317-295	0.44 [0.017]	7.5 [0.295]
13	2.92-KFD51320-590	0.50 [0.020]	15 [0.590]
14	2.92-KFD5132502	0.64 [0.025]	6.84 [0.269]
15	2.92-KFD5132501	0.64 [0.025]	10.92 [0.430]
16	2.92-KFD51325-1181	0.64 [0.025]	30 [1.181]
17	2.92-KFD51330	0.75 [0.030]	30 [1.181]
18	2.92-KFD51343-590	1.10 [0.043]	15 [0.590]
19	2.92-KFD51350-319	1.27 [0.050]	8.1 [0.319]
20	2.92-KFD51350-314	1.27 [0.050]	8 [0.314]
21	2.92-KFD51350-393	1.27 [0.050]	10 [0.393]

**Electrical & Environmental Characteristics**

Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~40GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f\_GHz}$
Operating Temperature	- 55~+165℃

**Material & Coat-Plating**

Inner Conductor	Beryllium Copper, Gold
Dielectric	PEI 1000
Body	Stainless Steel, Passivated
Coupling Nut	N/A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc		
		CHK			
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model		
		PRODUCT SPEC	2.92-KFD51350-393 2.92mm Female Flange Connector		
		APPLICATION SPEC			
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE OT8L4	DRAWING NO
		CUSTOMER DRAWING			SHEET 1 OF 1
					RVE 1