



No.	Model	Pin Size Ød
1	SMA-KFD80531	0.80 [0.031]
2	SMA-KFD80536	0.91 [0.036]
3		
4		
5		

Electrical & Environmental Characteristics

Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~26.5GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165℃

Material & Coat-Plating

Inner Conductor	Beryllium Copper, Gold
Dielectric	PTFE
Body	Stainless Steel, Passivated
Coupling Nut	N/A

THIS DRAWING IS A CONTROLLED DOCUMENT

DWN

CHK

Suzhou Talent Microwave, Inc

Unit
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED
 0 PLC ±0.25
 1 PLC ±0.15
 2 PLC ±0.12
 3 PLC ±
 3 PLC ±
 ANGLES ±1°

APVD

PRODUCT SPEC

APPLICATION SPEC

Product Model

SMA-KFD80531
SMA Female Flange Connector

MATERIAL
SEE TABLE

FINISH
SEE TABLE

WEIGHT

SIZE
A4

GAGE CODE
OT8L4

DRAWING NO

CUSTOMER DRAWING

SHEET 1 OF 1

RVE 1