






Flat needle direction①



Flat needle direction②

Electrical & Environmental Characteristics

Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~26.5GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165℃

Material & Coat-Plating

Inner Conductor	Beryllium Copper, Gold
Dielectric	PTFE
Body	Stainless Steel, Passivated
Coupling Nut	Stainless Steel, Passivated

No.	Model	D(Diameter)	L(Length)	T(Thickness)	
1	SMA-JFD40614	1.27 [0.050]	1.27 [0.050]	0.15 [0.006]	①
2	SMA-JFD406C14	1.27 [0.050]	1.27 [0.050]	0.15 [0.006]	②
3					
4					

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave,Inc					
		CHK						
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ±- 3 PLC ±- ANGLES ±1°	APVD	Product Model SMA-JFD406C14 SMA male Flange Connector					
		PRODUCT SPEC						
		APPLICATION SPEC						
		SIZE A4						GAGE CODE 0T8L4
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT						
		CUSTOMER DRAWING				SHEET1 OF 1		RVE 1