

## SPDT, Terminated, Coaxial Switches

R12-SF12018-TI, Coaxial Switches, SPDT, SMA, Failsafe, 12VDC, DC to 18 GHz, Solder Pin, Terminated, Electronic Type Indicator

R12-SF24018-TI, Coaxial Switches, SPDT, SMA, Failsafe, 24VDC, DC to 18 GHz, Solder Pin, Terminated, Electronic Type Indicator

R12-SF28018-TI, Coaxial Switches, SPDT, SMA, Failsafe, 28VDC, DC to 18 GHz, Solder Pin, Terminated, Electronic Type Indicator

### 电气参数 Electrical Characteristics:

参数 Parameter	条件 Condition
频率范围 Frequency range	DC-18 GHz
阻抗 Impedance	50 Ω
开关模式 Operation mode	Failsafe
开关顺序 Switch sequence	Break before make
切换时间 Switching time	15 ms max
机械寿命 Mechanical life	1 million min
负载功率 Termination power CW	0.5W
额定电压 Rated voltage	12 24 28 VDC
工作电流 Operating current at 23 °C	380 200 170 mA
指示灯额定值 Indicator rating	Electronic Type Indicator Max withstand voltage: 60VDC Max current capacity: 100mA Max "ON" resistance: 16Ω Note: VDCi and COM- must be connected to operate.



### 射频特性 RF Specifications:


频率范围 FREQUENCY RANGE(GHz)	DC-6	6-12	12-18
插入损耗 INSERTION LOSS (MAX) dB	0.2	0.25	0.4
隔离度 ISOLATION (MIN) dB	70	70	60
电压驻波比 V.S.W.R. (MAX)	1.2:1	1.3:1	1.4:1

### 环境和物理特性 Environmental And Physical Characteristics:


参数 Parameter	条件 Condition
工作温度范围 Operating temperature range	-25°C to +65°C(Standard ) -55°C to +85°C(Optional)
振动 Sine vibration(Operating)	20-2000Hz, 10g
冲击 Shocks(Non Operating)	50g / 11ms, ½ sine
射频接口 RF Connector type	SMA Female
控制接口 Control connector	Solder Pin
重量 Weight	88g Max
外壳颜色 Housing Color	浅蓝色 Light Blue

备注: 如果客户需要其他外壳颜色, 请联系业务备注

**外形尺寸 Outline Drawing:** Unit: mm




**原理图 Schematic:**




This graph is based on the following conditions:

- Ambient temperature: + 25 °C
- Sea level
- V.S.W.R.: 1 and cold switching

**功率曲线图 Average power:**



针脚定义 Pin Definition:




Solder Pin		RF Connect Used
Pin NO.	Function	SPDT
1	+VDC	NO:J1-COM
	0	NC:J2-COM
2	UNUSED	
3	COM-	
4	VDCi	
5	1(IND.)	NO:J1-COM
6	COMi(IND.)(V+)	
7	2(IND.)	NC:J2-COM

标准型号 Part Number:


标准型号 Part Number	额定电压 Rated Voltage	可选项 Option
SPDT		
R12-SF12018-TI	12VDC	-S
R12-SF24018-TI	24VDC	例如:R12-SF12018-TIS
R12-SF28018-TI	28VDC	(备注, S型号满足IP65)

**典型曲线 Typical Performance Data:**

INSERTION LOSS



VSWR



ISOLATION

