

Power Amplifier

0.7-6GHz /47dB Gain/47 dBm Psat

Model: TLPA0.7G6G-47-47

TLPA0.7G6G-47-47 is a power amplifier with power gain of 47 dB and a nominal Psat of 47 dBm across the frequency range of 0.7 to 6 GHz. The DC power requirement for the amplifier is +36 VDC/400 W. The input port configuration offers coax adapter structure with SMA female and output port configuration offers coax adapter structure with N female.

Features:

- Ultra Wide Band: 0.7-6GHz
- Gain: 47dB Min
- Output Power Psat: 47dBm Min
- Protection: over voltage protection
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.7-6			GHz
功率增益 Power Gain	47			dB
增益平坦度 Gain Flatness		±3		dB
饱和输出功率 Output Psat	47			dBm
杂散 Spurious@Pout=47dBm			-60	dBc
谐波抑制 Harmonic@Pout=47dBm			-10	dBc
输入驻波 Input VSWR			2	:1
直流电压 DC Voltage		36		V DC
功耗 Power Consumption			400	W
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/N Female	
直流偏置 DC Bias	D-SUB7W2	A1:+36V A2:GND Pin1~5:NC
尺寸 Size	262*182*107.5(With heatsink)	mm
重量 Weight	/	g

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+36 V
输入功率 RF Input Power	+10 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+50	°C
存储温度 Non-operating Temperature*	-50		+60	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA0.7G6G-47-47	Power amplifier 0.7-6 GHz,Gain:47dB,Psat:47dBm, +36 V DC,Without Heatsink	
TLPA0.7G6G-47-47-HS	Power amplifier 0.7-6 GHz,Gain:47dB,Psat:47dBm, +36 V DC,With Heatsink	Rev.1.1

典型曲线 Typical Performance Data:


Input VSWR vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Small Signal Gain vs Frequency



P1dB vs Frequency




Pout@Pin




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Pout@Equal_Pin



Spurious vs Frequency



Harmonic vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.