

Power Amplifier

0.7-18GHz /37dB Gain/37 dBm Psat

Model: TLPA0.7G18G-37-37

TLPA0.7G18G-37-37 is a power amplifier with power gain of 37 dB and a nominal Psat of 37 dBm across the frequency range of 0.7 to 18 GHz. The DC power requirement for the amplifier is +28 VDC/3 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Ultra Wide Band: 0.7-18GHz
- Gain: 37dB Min
- Output Power Psat: 37 dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.7-18			GHz
功率增益 Power Gain	37			dB
增益平坦度 Gain Flatness			±2.5	dB
饱和输出功率 Output Psat	37			dBm
杂散 Spurious@Pout=37dBm			-60	dBc
谐波 Harmonic@Pout=37dBm		-15	-10	dBc
输入驻波 Input VSWR			2	:1
直流电压 DC Voltage		28		V DC
直流电流 DC Supply Current			3	A
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	J30J-9ZKP	
尺寸 Size	150*90*20	mm
重量 Weight	≤1	Kg

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	TBD
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

直流供电接口 DC Supply Connector(J30J-9ZKP):

引脚 Pin	功能 Function	引脚 Pin	功能 Function
1~2	NC	5*	TTL-SWITCH
3	CURRENT SENSOR	6~7	+28V
4	TEMP SENSOR	8~9	GND

*Note: 'High' DC power setting on,'Low' DC power setting off.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	℃
存储温度 Non-operating Temperature*	-50		+70	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA0.7G18G-37-37	Power amplifier 0.7-18GHz,Gain:37dB,Psat:37dBm, +28V DC,Without Heatsink	Rev.1.1
TLPA0.7G18G-37-37-HS	Power amplifier 0.7-18GHz,Gain:37dB,Psat:37dBm, +28V DC,With Heatsink	Rev.1.1