

Power Amplifier

24-27.5GHz /43dB Gain/43 dBm Psat

Model: TLPA24G27.5G-43-43

TLPA24G27.5G-43-43 is a power amplifier with power gain of 43 dB and Psat of 43 dBm across the frequency range of 24 to 27.5 GHz. The DC power requirement for the amplifier is +22 VDC/12 A. The input and output port configuration offers coax adapter structure with 1.85mm female.

Features:

- Ultra Wide Band: 24-27.5 GHz
- Gain: 43dB Min
- Output Power Psat: 43dBm Min
- Protection: Over TEM, over voltage, over current protection
- Can withstand total reflection for a long time
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	24-27.5			GHz
功率增益 Power Gain	43			dB
增益平坦度 Gain Flatness		±3		dB
饱和输出功率 Output Psat	43			dBm
杂散 Spurious@Pout=43dBm			-60	dBc
谐波抑制 Harmonic@Pout=43dBm			-20	dBc
直流电压 DC Voltage	20	22	24.5	V DC
直流电流 DC Supply Current			12	A
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入接口 Input Connector	2.92mm Female	
*输出接口 Output Connector	WR42/WR34/2.92mm Female	
直流供电接口 DC Supply Interface	DSUB-2W2	A1:+22V A2:GND
尺寸 Size	230*194*85(With Heatsink)	mm
重量 Weight	≤7	Kg


*Note: Users can choose freely and J30J-9ZKP no connection.

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+24.5 V
输入功率 RF Input Power	+10 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+50	°C
存储温度 Non-operating Temperature*	-30		+60	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA24G27.5G-43-43	Power amplifier 24-27.5GHz,Gain:43dB,Psat:43dBm, +22V DC,Without Heatsink	Rev.1.1
TLPA24G27.5G-43-43-HS	Power amplifier 24-27.5GHz,Gain:43dB,Psat:43dBm, +22V DC,With Heatsink	Rev.1.1


典型曲线 Typical Performance Data:




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Small Signal Gain vs Frequency



PndB vs Frequency




Pout@Pin




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Pout@Equal_Pin



Spurious vs Frequency



Harmonic vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.