

Low Noise Amplifier

0.5-67GHz /5.0dB NF/25dB Gain/15 dBm P1dB

Model: TLLA0.5G67G-25-50

TLLA0.5G67G-25-50 is a low noise amplifier with a typical small signal gain of 25 dB and a nominal noise figure of 5.0 dB across the frequency range of 0.5 to 67 GHz. The DC power requirement for the amplifier is +6 V DC/100 mA. The input and output port configuration offers coax adapter structure with 1.85mm female.

Features:

- Ultra Wide Band:0.5-67GHz
- Gain: 25dB Typ
- Noise Figure: 5.0dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.5		67	GHz
增益 Gain		25		dB
增益平坦度 Gain Flatness		±2.0		dB
噪声系数 Noise Figure		5.0		dB
线性输出功率 Output P1dB		15		dBm
输出三阶交调 Output IP3		20		dBm
输入驻波 Input VSWR		2		:1
输出驻波 Output VSWR		2		:1
直流电压 DC Voltage		6	12	V DC
直流电流 DC Supply Current		100		mA
阻抗 Impedance	50			Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	1.85mm Female/1.85mm Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	44.8*29.2*11	mm

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+12 V
输入功率 RF Input Power	+10 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm



*****Heat Sink Required During Operation**



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:


标准型号 Base Number	描述 Description	版本号 Revision
TLLA0.5G67G-25-50	Low Noise Amplifier, 0.5-67GHz, Noise Figure:5.0dB, Gain:25 dB,P1dB:15dBm,+6V DC,Without Heatsink	Rev.1.1
TLLA0.5G67G-25-50-HS	Low Noise Amplifier, 0.5-67GHz, Noise Figure:5.0dB, Gain:25 dB,P1dB:15dBm,+6V DC,With Heatsink	Rev.1.1

典型曲线 Typical Performance Data:

Gain&VSWR vs Frequency




Noise Figure vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Gain vs Output Power



P1dB vs Frequency



P3dB vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.