

Power Amplifier

1-18GHz/30dB Gain/31 dBm Psat

Model: TLPA1G18G-30-30

TLPA1G18G-30-30 is a power amplifier with a small signal gain of 30 dB and a nominal Psat of 31 dBm across the frequency range of 1 to 18 GHz. The DC power requirement for the amplifier is +18 VDC/1 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Ultra Wide Band: 1-18 GHz
- Gain: 30dB Min
- Output Power Psat: 31dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	1-18			GHz
小信号增益 Small Signal Gain	30			dB
增益平坦度 Gain Flatness		±2	±2.5	dB
线性输出功率 Output P1dB	30			dBm
饱和输出功率 Output Psat		31		dBm
噪声系数 Noise Figure			5	dB
杂散 Spurious		-60		dBc
输入驻波 Input VSWR		2	2.2	:1
输出驻波 Output VSWR		2	2.2	:1
直流电压 DC Voltage		18	20	V DC
直流电流 DC Supply Current		1		A
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	58.5*38*12	mm
重量 Weight	50	g

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+20 V
输入功率 RF Input Power	+6 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:


标准型号 Base Number	描述 Description	版本号 Revision
TLPA1G18G-30-30	Power amplifier 1-18GHz,Gain:30dB,Psat:31dBm, +18V DC,Without Heatsink	Rev.1.1
TLPA1G18G-30-30-HS	Power amplifier 1-18GHz,Gain:30dB,Psat:31dBm, +18V DC,With Heatsink	Rev.1.1

典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.