

Power Amplifier

WR-10/75-90GHz/17dB Gain/16dBm Psat**Model: TMPA-075090-1716-10**

TMPA-075090-1716-10 is a power amplifier with a typical gain of 17 dB and a nominal Psat of 16 dBm across the frequency range of 75 to 90 GHz. The DC power requirement for the amplifier is +12 VDC/70 mA. The input and output port configuration offers an inline structure with WR-10 waveguides and UG-387/U-M anticocking flanges.

Features:

- Frequency range: 75-90GHz
- Gain: 17dB Typ
- Output Power Psat: 16dBm Typ
- Good Power and Gain Flatness

Applications:

- Passive Imaging
- Communication Systems
- Radar Systems

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency range	75-90			GHz
Gain		17		dB
Output Psat		16		dBm
Input VSWR		2.3		:1
Output VSWR		2		:1
DC Voltage		12		V DC
DC Supply Current		70		mA

Mechanical Specifications:

Parameter	Value	Units
Input /Output Connector	WR-10/UG-387/U	
DC Bias	Solder Pin	
Size	30*30*23	mm


Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	+15 V
RF Input Power	+10 dBm
ESD sensitivity (HBm)	Class 0, passed 150V

Outline Drawing:

Unit:mm

Regulatory Compliance:



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.


Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature	-10		+65	°C
Non-operating Temperature	-45		+85	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

Ordering Information:


Base Number	Description	Revision
TMPA-075090-1716-10	Power Amplifier, 75-90GHz, Gain: 17dB Type, P _{sat} : 16dBm Type, +12V DC,WR-10	Rev.1.1

Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.