

Power Amplifier

2-18GHz/43dB Gain/43dBm Psat

Model: TLPA2G18G-43-43

TLPA2G18G-43-43 is a power amplifier with a minimum small signal gain of 43 dB and a typical Psat of 43 dBm across the frequency range of 2 to 18 GHz. The DC power requirement for the amplifier is +28 VDC/5 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 2-18GHz
- Gain: 43dB Min
- Output Power Psat: 43dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency range	2-18			GHz
Small Signal Gain	45			dB
Gain Flatness		±3		dB
Output Psat	42.5	43		dBm
Spurious			-50	dBc
Harmonic			-10	dBc
Input VSWR			2	:1
DC Voltage		28		V DC
DC Supply Current			5	A
Impedance	50			Ohms

Mechanical Specifications:




Parameter	Value	Units
Input /Output Connector	SMA Female/SMA Female	
DC Supply Connector	Feedthru capacitors	
Size	60*60*11(Without heatsink) 188*125*146(With heatsink)	mm
Weight	≤200	g

Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	+29 V
RF Input Power	+3 dBm
ESD sensitivity (HBm)	Class 0, passed 150V

Outline Drawing:

Unit:mm



Regulatory Compliance:



*****Heat Sink Required During Operation**



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature*	-40		+50	°C
Non-operating Temperature*	-50		+60	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


*Note: For a wider temperature range, please consult the manufacturer.

Ordering Information:

Base Number	Description	Revision
TLPA2G18G-43-43	Power amplifier 2-18GHz, Gain:43dB,Psat:43dBm,+28V DC,Without Heatsink	Rev.1.1
TLPA2G18G-43-43-HS	Power amplifier 2-18GHz, Gain:43dB,Psat:43dBm,+28V DC,With Heatsink	Rev.1.1

Typical Performance Data:


P1dB vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:


Pout@Equal_Pin



Pin@Psat vs Frequency




Spurious vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.