

Coaxial Termination

DC-50GHz/2.4mm Female/1W

Model:TT1-50-2.4-S-F

The TT1-50-2.4-S-F is a well-matched, 50Ω female termination enabling operation from DC to 50 GHz. This termination features a 1W power rating and 1.3:1 max VSWR.

Features:

- Operating Frequency DC to 50 GHz
- High Return Loss
- Instrumentation Grade

Applications:

- laboratory test
- Communication equipment


电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency Range	DC		50	GHz
驻波 VSWR			1.3	:1
耐功率 Power Handling			1	W
阻抗 Impedance		50		Ohms

环境和机械特性 Envriionmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
操作温度 Operating Temerature	-55 To +125	℃
存储温度 Storage Temperature	-55 To +125	℃
壳体材质 Body Material	Stainless Steel 303	
中心导体 Center Conductor	Becu, Golden	
接口 Connectors	2.4mm Female	
相对湿度 Relative Humidity	0-90%	

外形图 Outline Drawing: Unit:mm



订货信息 Ordering Information:

标准型号 Base Number	描述 Description
TT1-50-2.4-S-F	DC-50GHz,1W,2.4mm female Coaxial Termination